

Wireless Solutions

Specification www.acantenna.com

5.1-5.8GHz WIFI Outdoor 24dBi Die Cast Grid Antenna

Part No:AC-D5158G24-0304

1. Introduction

5.1GHz-5.9GHz Applications WiMAX,CDMA 802.11 a WiFi Networks Frequency Ultra-wide Wireless Lan Systems Public Wireless Hotspot 802.16WiMax .

Networks Directional and multipoint applications Superior Performance Good appearance designs

Outdoor antenna for public Hot spots Installed for vertical or horizontal polarization Heavy Duty

mounting .The reflector dish of these antennas are constructed from high quality aluminum which gives
them superior strength.The grud is coated in a light gray UV-inhibited polymer for durability and
aesthetics.Two piece reflector grid is simple to assemble and significantly reduces shipping costs.





Wireless Solutions

Specification www.acantenna.com

2. Specification

<u>'</u>	
Electrical	
Frequency Range	5150-5850MHz
F/B Ratio	≥20dB
Gain	24dBi
V.S.W.R	≤2.0
Radiation	Direction
Horizontal Beam width	9°
Vertical Beam width	12°
Polarization	Vertical or Horizontal
Lightning Protection	DC Grounded
Maximum Input Power	100W
Impedance	50Ώ
Impedance Connector	50Ω N Female
·	
Connector	N Female
Connector Antenna Radome Material	N Female Aluminum Alloy
Connector Antenna Radome Material Mounting way	N Female Aluminum Alloy Pole Mount
Connector Antenna Radome Material Mounting way Diameter of Installation Pole	N Female Aluminum Alloy Pole Mount
Connector Antenna Radome Material Mounting way Diameter of Installation Pole Mechanical	N Female Aluminum Alloy Pole Mount Ø50~Ø70mm
Connector Antenna Radome Material Mounting way Diameter of Installation Pole Mechanical Dimensions	N Female Aluminum Alloy Pole Mount Ø50~Ø70mm 300x400mm
Connector Antenna Radome Material Mounting way Diameter of Installation Pole Mechanical Dimensions Weight	N Female Aluminum Alloy Pole Mount Ø50~Ø70mm 300x400mm 1.4KG
Connector Antenna Radome Material Mounting way Diameter of Installation Pole Mechanical Dimensions Weight Operating Temperature	N Female Aluminum Alloy Pole Mount Ø50~Ø70mm 300x400mm 1.4KG -40°C to+70°C