

Wireless Solutions

Specification www.acantenna.com

4G/LTE 698-2700MHz Ultra Wideband Omni-Direction Antenna Part No:AC-Q7027F04

1. Introduction

This antenna is ideal for downtown urban settings, RV's or marine installations.

It's built with a strong fiberglass casing and is designed to cover 2G/3G/4Gand WLAN systems for Cellular, PCS, AWS and LTE frequencies.

This Full Band Fiberglass antenna is an omni-directional antenna that gathers signals from all sides and does not need to be pointed toward a cellular tower.

Parts includes mounting equipment for either a flat horizontal surface or a wall.

It shall be mounted in an upright position for best results.







Wireless Solutions

Specification www.acantenna.com

2. Specification

Electrical	
Frequency Range	698-960/1710-2700MHz
Gain	3/4dBi
V.S.W.R	≤2.5
Radiation	Omni-Direction
Horizontal Beam width	360°
Vertical Beam width	35°
Polarization	Vertical
Lightning Protection	DC Grounded
Maximum Input Power	100W
Impedance	50Ώ
Impedance Connector	50Ω N Male
Connector	N Male
Connector Antenna Radome Material	N Male Fiberglass
Connector Antenna Radome Material Mount way	N Male Fiberglass
Connector Antenna Radome Material Mount way Mechanical	N Male Fiberglass N Male Directly
Connector Antenna Radome Material Mount way Mechanical Dimensions	N Male Fiberglass N Male Directly Φ20x200mm
Connector Antenna Radome Material Mount way Mechanical Dimensions Weight	N Male Fiberglass N Male Directly Φ20x200mm 108g
Connector Antenna Radome Material Mount way Mechanical Dimensions Weight Operating Temperature	N Male Fiberglass N Male Directly Φ20x200mm 108g -40℃ to+70℃