

Wireless Solutions

Specification www.acantenna.com

4G/LTE 10dBi Panel Antenna With N Female Connector

Part No:AC-D7027W13-10P

1. Introduction

The IP65-rated High-Gain LTE Panel Directional Antenna is made from weatherproof and corrosion-resistant material, and is suited for both indoor and outdoor applications.

LTE Panel Directional Antenna extends the coverage range of a wireless network in a single direction. It is ideal for delivering extended access range.





Wireless Solutions

Specification www.acantenna.com

2. Specification

Frequency Range 698-960/171 Gain 7/10dBi F/B Ratio 15/20dB V.S.W.R ≤1.8 Radiation Direction Horizontal Beam width 70°/75° Vertical Beam width 75°/60° Polarization Vertical Lightning Protection DC Grounder Maximum Input Power 50W Impedance 50Ω Connector N Female Cable Length RG58U 30cm Antenna Radome Material ABS	
F/B Ratio V.S.W.R ≤1.8 Radiation Direction Horizontal Beam width 70°/75° Vertical Beam width 75°/60° Polarization Lightning Protection Maximum Input Power Impedance Connector N Female Cable Length 15/20dB 15/20dB 15/20dB	t
V.S.W.R ≤1.8 Radiation Direction Horizontal Beam width 70°/75° Vertical Beam width 75°/60° Polarization Vertical Lightning Protection DC Grounder Maximum Input Power 50W Impedance 50Ω Connector N Female Cable Length RG58U 30cm	ż
RadiationDirectionHorizontal Beam width70°/75°Vertical Beam width75°/60°PolarizationVerticalLightning ProtectionDC GrounderMaximum Input Power50WImpedance50ΩConnectorN FemaleCable LengthRG58U 30cm	ż
Horizontal Beam width70°/75°Vertical Beam width75°/60°PolarizationVerticalLightning ProtectionDC GrounderMaximum Input Power50WImpedance50ΩConnectorN FemaleCable LengthRG58U 30cm	t
Vertical Beam width75°/60°PolarizationVerticalLightning ProtectionDC GrounderMaximum Input Power50WImpedance50ΩConnectorN FemaleCable LengthRG58U 30cm	t
Polarization Vertical Lightning Protection DC Grounder Maximum Input Power 50W Impedance 50Ω Connector N Female Cable Length RG58U 30cm	k
Lightning Protection DC Grounder Maximum Input Power 50W Impedance 50Ω Connector N Female Cable Length RG58U 30cm	t
Maximum Input Power50WImpedance50ΩConnectorN FemaleCable LengthRG58U 30cm	t
Impedance 50Ω Connector N Female Cable Length RG58U 30cm	
Connector N Female Cable Length RG58U 30cn	
Cable Length RG58U 30cn	
Antenna Radome Material ABS	1
Mount way Pole mount	
Diameter of Installation Pole Ø30~Ø50mn	1
Mechanical	
Dimensions 300x183x70r	nm
Weight 754g	
Operating Temperature -40℃ to+60℃	
RoHS Compliant YES	2