



Specification www.acantenna.com

## **GPS/GSM Stick Mount Combination Antenna With Fakra Connector**

# Part No:AC-GPS/GSM-05

#### 1. Introduction

The GPS/GSM combo antennas have been designed to provide maximum performance and versatility for telematics applications, including fleet monitoring and asset tracking.

The antennas precise performance and easy of installation provides outstanding value and flexibility for the most demanding wireless mobile applications.

Magnetic mount, and permanent adhesive mount will be choose.

It is good use to put it on top of the car, and then take it for travel.





# **Wireless Solutions**

Specification www.acantenna.com

### 2. Specification

2. Specification		
Electrical		
GPS Part:	Dielectric Antenna	
	Frequency Range	1575.42MHz±3 MHz
	Polarization Type	RHCP
	Gain	5dBi
	V.S.W.R	<1.5
	Impedance	50Ώ
	LNA	
	LNA Gain	30dB Typical
	Noise Figure	1.5dB
	Ex-band Attenuation	12dB@CF+50MHz/16dB@CF-50MHz
	V.S.W.R	<2.0
	Voltage	2.7/3.0/3.3/5.0/3.0 to 5.0 etc.
	Current Consumption(mA)	11 Max
GSM Part:	Frequency range	824-960/1710-2170MHz
	V.S.W.R	<2.0
	Gain	2dBi
	Polarization	Linear
	Impendance	50Ω
Mechanical		
	Housing	Black
	Cable	2xRG174
	Length	2x3/5M or can be customization
	Connector	2xSMA Male or can be customization
Environmental		
	Working Temp	-40℃~+80'℃
	Humidity	55%-75%RH
	Waterproof	IP67(Not include the line port)
	Antenna Radome Material	ABS
	Mount way	Adhesive
	Antenna Dimension	95x35x14mm
	Weight	230g
	RoHS Compliant	YES